

FIRE ALARM SYSTEM



SIEMENS



BC8001

- Compact wall-mounted design
- Each control unit connects up to 2 lines, 127 points per line, in total 254 points
- Multi-language user interface with backlit LCD display (240 x 128 pixels)
- Configuration is done through Windows based application, software downloaded via USB port to the control unit



BC8002

- Text and graphic display on large illuminated 10" LCD
- Easy operation with a Windows Explorer like menu structure
- Each control unit connects up to 16 lines, 127 points per line, in total 2032 points
- 8 mid-line interlocking outputs for key equipment
- Remote communications through modems



Comprehensive Control

- 2 x BC8002 with 16 detection lines
- 1 x BC8001 (Compact Model) with 2 detection lines
- All panels share data on a peer-to-peer network
- System monitors 1,000 smoke and heat detectors
- System monitors 100 manual call points
- 72 input and output control points

NOTIFIER
by Honeywell



411 Series Communicator

- Three models available
- 411 - Slave Communicator
- 411UD - Slave Communicator with up download
- 411UDAC - Standalone Communicator with up/download
- Up to four input channels (1 on the 411)
- Fully programmable via RPRO-411 or with Windows® utility (up/download models)



SP-2000 4-Zone Control

- Four Class B Notifying Device Circuits (Class B with Class A option module)
- Two class B Notifying Appliance Circuits, 600 amps, with Class A option and programmable strobe synchronization
- 1/4" Ready - conventional detection with drift compensation and maintenance alert
- Form-C, Alarm, Trouble and Supervisory relays



SP Series Relaying Controls

- Two models - RP1001 for pre-action deluge, RP1002 for agent release
- Four zones - cross, abort and manual release
- Four Notifying Appliance Circuits - 2 for release, 2 for warning



SP-1024 16-Zone Control Communicator

- 16 Class B zones (Class A with option module)
- Built-in digital communicator
- 2 Notifying Appliance Circuits, expandable to 4 (6.0 amps)



HOCHIKI
america corporation



ALPH PHOTOELECTRIC SMOKE SENSOR



ATGEA HEAT SENSOR



SLR-24V SMOKE DETECTOR



CDM - CONVENTIONAL ZONE MODULE



FireNET 4127 ANALOG ADDRESSABLE FIRE ALARM CONTROL PANEL




HCP-1000RS FIRE ALARM CONTROL PANEL



HPS-CP CALL POINT BREAK GLASS STATIONS



HPS-CP-5 CALL POINT BREAK GLASS STATIONS



HPS-CP-5 CALL POINT BREAK GLASS STATIONS



HPS-CP-5 CALL POINT BREAK GLASS STATIONS

Hochiki America's Models HPS series pull stations are available in six models:

- HPS-SAH single action
- HPS-SAR single action with key lock
- HPS-DH dual action
- HPS-DH dual action with key lock
- HPS-DH dual action with key lock (openable)

FIRELITE Alarms
by Honeywell

