

FIRE SECURITY SYSTEM



CCTV SYSTEM



Exite®

Exite® offers you an outstanding PTE service with integrated camera/monitor making the installation of 200 types of cameras in hospitals, schools and other. With many high speed dials, 2.0 mm to 10.0 mm and provide the view with a powerful PTE device for television view.

Spectra IV

Spectra IV is the ideal choice for your most critical applications where you demand the speed, accuracy and superior image quality that can only be found in Spectra. Additional features not found in the other systems include Electronic Image Stabilization and Image Enhancement.

CM780 Series Matrix

MICROPROCESSOR-BASED SWITCHER/CONTROLLER, 4096 INPUTS, 512 OUTPUTS



SAMSUNG

SNR-6400/3200



4x/2x Optical Zoom/5/10mm Zoomer
Record up to 1024 pixels, Video storage Record up to 1.0MB, 1.5MB, 2.0MB at 1/25" resolution
S/N Ratio: 40dB, 45dB, 50dB, 55dB
Support 1024 x 768, 640 x 480
CDS management software
Invert LCD monitor for easy configuration

SNR-1300



High Performance Megapixel Camera
Real time 1024 x 768 pixel video
Built-in 1.32 megapixel CCD sensor
Power over Ethernet
High resolution images 1,080 x 720p
EXTENDED, 1/25, 1/30, 1/60, 1/125, 1/250
High Resolution 1024 x 768
4:3, 16:9, 16:10, 16:9

SNP-3750



3CCD High Resolution 1080P/720P
Built-in 1024 x 768 pixel video
Built-in 1.32 megapixel CCD sensor
Power over Ethernet
High resolution images 1,080 x 720p
EXTENDED, 1/25, 1/30, 1/60, 1/125, 1/250
High Resolution 1024 x 768
4:3, 16:9, 16:10, 16:9

25632



Wide Angle Monitor
Real time 1024 x 768 pixel video
Built-in 1.32 megapixel CCD sensor
Power over Ethernet
High resolution images 1,080 x 720p
EXTENDED, 1/25, 1/30, 1/60, 1/125, 1/250
High Resolution 1024 x 768
4:3, 16:9, 16:10, 16:9

SCC-1000



PTE Control Keyboard
Control up to 256 PTE cameras
Real time 1024 x 768 pixel video
Built-in 1.32 megapixel CCD sensor
Power over Ethernet
High resolution images 1,080 x 720p
EXTENDED, 1/25, 1/30, 1/60, 1/125, 1/250
High Resolution 1024 x 768
4:3, 16:9, 16:10, 16:9

STM-421/321



421, 321, 1/25, 1/30, 1/60, 1/125, 1/250
High Resolution 1024 x 768
4:3, 16:9, 16:10, 16:9

SANYO

products line up

	Day / Night	TV Lines	Min. Ill.	Lens
VCC-D250P	Color	480 TV Lines	0.3 lx	3.7 mm
VCC-D1573PA	Color	520 TV Lines	1.9 lx	Par-Focal lens
VCC-P9575P	Color	520 TV Lines	1.9 lx	Par-Focal lens
VCC-D250P	Color	480 TV Lines	0.3 lx	f=2.8 to 8.0 mm
VCC-C1575VP	Color	520 TV Lines	1.0 lx	1.8x-9.0x 1/2" Super Var-Focal lens
VCC-P688VP	Color	520 TV Lines	0.5 lx	3.0x-9.0x 1/2" Super Var-Focal lens







ACCESS CONTROL SYSTEM

SIEMENS

SIPASS ENTRO



HOW TO SYSTEMS



Honeywell

WPABV1

Access, Video, 128 Zone Intrusion Integration Kit for Ethernet Based Communications 2 door access control panel (DC2P) includes plug-in transformer and 5-1 suppressors, digital video records



FACILITY COMMANDER

Facility Commander is the first product to offer a variety of integration options. You can make use of its included drivers for multiple access control, digital video, alarm, and other security and facility management systems.







EMERGENCY SYSTEM

EMERGENCY LIGHT

FLAME RETARDANT CASE (CP-M SERIES)

STANDARD CASE (MB SERIES)

DICHROIC HALOGEN

COMPACT-SLIM TYPE

STANDARD LEGEND

